



**Putzmeister**

## Your benefits

- 4 cylinder engine for maximum power
- Hydraulic feeder to work more efficiently
- Scaper to fill easily
- Operating panel clear and user-friendly
- Chassis with automatic brake adjustment
- Optimised maintenance and service features
- Robust design ensures value retention and high resale values
- Made in Germany

## Mixokret M 760 – Maximum engine power for challenging tasks



The perfect interaction of engine, compressor and hydraulic mixer drive gives the Mixokret M 760 its high performance. Large construction sites with up to 50 stories or 200 m horizontal – no problem for the Mixokret M 760.

The compressor ensures that the pump operates more consistently and wear resistant. In other words, it maintains a constant material flow and reduces movements of the delivery hoses.

The oil-cooled 4-cylinder Deutz diesel engine is one of the most reliable of its kind. In idling speed, the engine regulates its speed automatically down. This makes it more quiet, saves fuel and has lower wear.

For further information related to technical details or application, please contact your local Putzmeister dealer.

- **Cement screed**
- **Calcium sulphate screed (anhydrite)**
- **Magnesia screed**



Semi-dry  
floor screed



Oil-cooled 4-cylinder Deutz diesel engine with an efficient compressor for maximum pump output, and enough reserve power for more challenging jobs



Air valve fitting, instruments and important indicators are all within view and easy to reach



The innovative exhaust air routing and an additional exhaust duct improve the working area.

## Technical data

	M 760 DH	M 760 DHB	M 760 DHBS
<b>Mixer drum</b>	260 l, 200 l useful cap.	260 l, 200 l useful cap.	260 l, 200 l useful cap.
<b>Delivery rate*</b>	4 m <sup>3</sup> /h	4.8 m <sup>3</sup> /h	5 m <sup>3</sup> /h
<b>Delivery pressure</b>	8 bar	8 bar	8 bar
<b>Delivery range**</b>	200 m horizontally / 150 m vertically (50 storeys)		
<b>Compressor</b>	5.0 m <sup>3</sup> /min; cut-off pressure 8 bar		
<b>Engine</b>	4-cylinder Deutz diesel; 46 kW at 2,600 rpm (not available in the EU)		
<b>Weight (fully fuelled)</b>	1,720 kg	1,826 kg	1,900 kg
<b>Tank capacity</b>	60 l	60 l	60 l
<b>Length</b>	4,780 mm	5,075 mm	5,075 mm
<b>Width</b>	1,480 mm	1,480 mm	1,480 mm
<b>Height</b>	1,520 mm	2,431 mm	2,431 mm
<b>Filling height</b>	820 mm	400 mm	400 mm
<b>Maximum grain size</b>	16 mm	16 mm	16 mm
<b>Chassis</b>	braked, with automatic brake adjustment approved for speeds up to 80 km/h		
<b>Special feature</b>	Basis version	with hydraulic feeder	with hydraulic feeder and scraper

\* The delivery rate is theoretical and depends on the pump pressure.

\*\* The data is based on experience and depends on the material properties.

## Equipment

Automatic brake adjustment	■
Car coupling	■
Central lubrication system	■
Discharge stand	■
Grease pump for lubrication system	■
Instruction manual and spare parts list	■
Lever Press with hose	■
Lifting eye	■
Reservoir gauge in control panel	■
Working lights	■
Auto-Power-Off	□
Conversion to 100 km/h	□
High-pressure cleaner	□
Light holder 24 V	□
Location system	□
Mixing time adjustment	□
Performance management	□
Special canopy paint in RAL colours/Custom labelling	□
Support feet	□
Truck coupling	□
Wear plates at the dome	□
Wear plates front end (impact protection bars)	□
Wear plates, highly wear-resistant (lateral)	□
Wear plates, plastic	□

□ Optional ■ Standard

## Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany  
P.O.Box 2152 · 72629 Aichtal / Germany  
Tel. +49 7127 599-0 · Fax +49 7127 599-743  
mm@pmw.de · www.pmmortar.de

