



Liquid floor screed pump

TF300-D

New generation of liquid screed pump compliant with Stage V emission standard, compact, easy to handle, the ideal solution for small and medium-sized jobsites



- New modern design engineered especially for pumping liquid screed
- Machine equipped with diesel engine which complies with Stage V emission standard
- Designed with reliable and high quality components
- Low cost of ownership
- Simple to use. All range of options and equipments available
- Precise output adjustment (5 speeds) with remote control as standard on both models
- Corner grid specially designed for liquid floor screed providing an optimal and consistent material flow
- Perfectly balanced for easy handling on jobsite
- Comfortable road driving which holds the road well

Liquid floor screed pump

TF300-D



PERFORMANCE AND SIMPLICITY

- High performance machine compliant with Stage V emission standard
- High quality hydraulic system and transmission
- Ergonomic remote control and intuitive use
- Lightweight machine, unbrake axle, optimal balance



LOW COST OF OWNERSHIP

- Competitive purchase price and inexpensive machine using
- Rotor/stator lifespan improvement
- Robust machine, reliable and recognized components
- Few wear parts, fast and simple maintenance



CREATIVE TECHNOLOGY

- Automatic hoses decompression when stop pumping
- New corner grid suitable with all liquid floor screeds fibers
- Vibrating screen
- Audible pumping stop alarm



USER COMFORT

- Complete equipments: 1.5L71, high pressure cleaner, stabilizing
- Precise output adjustment (5 speeds) with remote control as standard
- Large fuel tank of 40 liters
- Grid choice available and easily replaceable
- Low noise emission when using et reinforced safety



DISTRIBUÉ PAR

TECHNICAL SPECIFICATIONS TF300-D

Performances	• Theoretical flow rate (*)	14 m ³ /heure
	• Maximum grain size	8 mm with 1.5L71
	• Maximum discharge distance (**)	100 m
Engine	• Liquid-cooled diesel engine	3-cyl. Kubota 18.5 kW Stage V
	• Variable flow hydraulic pump	Rexroth
Pumping	• Discharge hopper capacity	160 L
Capacities	• Diesel tank	40 L
Axle	Unbrake, road approvals	
Dimensions	• L x l x H (mm)	3 000 x 1 350 x 1 200

(*) The delivery rate is theoretical and depends on the pumping material properties and jobsite configuration.

(**) Maximal distance and depends on pumping materials properties.