

Stationary concrete pump

BSA 2109 H D

Output up to 95 m³/h
Delivery pressure up to 152 bar



Note: Standard version BSA 2109 H D. Dimensions and weights depend on equipment. Subject to technical modifications and errors.

Technical data

Model		BSA 2109 H D
Material number		102437.000
Output	m ³ /h	95 / 57 *
Delivery pressure	bar	91 / 152 *
Delivery cylinder	Ø mm	200
Delivery cylinder stroke	mm	2100
Strokes / minute		24 / 15 *
Engine power	kW	200
Hopper		RS 905 H
Capacity	l	approx. 600
Filling height	m	approx. 1.3
Transfer tube		S 2015 D
Line connection	mm	ZX 150
Pressure connection	"	8
Control system		EPS FFH
Weight	kg	6300

* Values for hydraulic fluid being fed to piston-side
All data maximum theoretical

Serial equipment

Agitator safety switch off	Gate valve connection
Cable remote control 10 m	Grill 60 mm
Central lubrication on hopper with hand lever press	Hard metal wear parts
Cleaning accessories	Operating manuals (1× paper, 1× CD-ROM) spare part list
Coloring: Pump, frame, roof, tank and hood anthracite-grey Cover chrome yellow	Outriggers 4× mech.
Concrete hopper with agitator	Pump flow meter
Concrete output adjust	Set-up foot mech.
Concrete pressure adjust	Speed drawdown automatically on pump stop
Coupling ring (DIN)	Splash guard
Drive diesel, Deutz 200 kW	Tool set incl. standard equipment
Electronic error management	Trailer F8, travelling in site
Ergonic Graphic Display (EGD)	
Flushing water pump 50 l/min 20 bar	

See quotation for exact serial delivery scope.
Comprehensive range of options available on request.