

BSF 31-5 (TRDI 80)

Support variants / Abstützvarianten



<p>Vorne / front 5,50 m</p> <p>S</p> <p>Hinten / rear 7,00 m</p>	<p>5,50 m</p> <p>F</p> <p>4,50 m</p>	<p>5,50 m</p> <p>Fs</p> <p>3,00 m</p>	<p>3,20 m</p> <p>F1</p> <p>4,50 m</p>	<p>3,20 m</p> <p>F1s</p> <p>3,00 m</p>	<p>4,60 m</p> <p>F2</p> <p>4,50 m</p>	<p>4,60 m</p> <p>F2s</p> <p>3,00 m</p>
<p>Vorne / front 4,00 m</p> <p>L</p> <p>Hinten / rear 5,80 m</p>	<p>4,00 m</p> <p>Ls</p> <p>5,00 m</p>	<p>4,30 m</p> <p>L1*</p> <p>5,80 m</p>	<p>4,30 m</p> <p>L1s</p> <p>5,00 m</p>	<p>5,10 m</p> <p>L2</p> <p>5,80 m</p>	<p>5,10 m</p> <p>L2s</p> <p>5,00 m</p>	
<p>Vorne / front 2,60 m</p> <p>O</p> <p>Hinten / rear 2,60 m</p>	<p>5,50 m</p> <p>LF</p> <p>5,80 m</p>	<p>5,50 m</p> <p>LFs</p> <p>5,00 m</p>				

26,3 m (BSF 31-5) Working range horizontal
Arbeitsbereich horizontal

18,4 m (BSF 31-5) Working range arm 1 vertical
Arbeitsbereich 1. Arm senkrecht

Support on left side (L) same as right side (R)
Abstützung links (L) gleich wie rechte Seite (R)
Support width based on center of support leg
Abstützbreite bezogen auf Mitte Stützfuß
F = frontal; s = narrow/schmal; S = Standard