

Concrete pump

BSF MOLI 1407 D RMC

Output up to 72 m³/h

Delivery pressure up to 97bar



Technical data for concrete pump

Model		BSF MOLI 1407 D RMC
Output	m ³ /h	72/48*
Delivery pressure	bar	65/97*
Delivery cylinder diameter	mm	200
Delivery cyl. stroke	mm	1400
Strokes / minute		27/18*
Drive power	kW	74
Hopper		RS 905A
Capacity	l	aprox. 600
Filling height	m	1.3
Transfer tube		S 2018 PN
Flap straight diameter	mm	150
Control system		OPS-RMC
Weight - Approx	Kg	6900

* Values for hydraulic fluid being fed to piston side

Scope of supply

Diesel engine, 74 kW, Kirloskar Air cooled
Hopper with agitator
Operating manuals and spare part lists 2x
Central lubrication strip, hopper
Cast wear parts, highly resistant
Chrome delivery cylinder
Rear Out triggers 2x hydraulically operated
Water tank 500L
Delivery pipes 100 mt set
Flushing water pump, 22 bar, easy for operation
Connection kit for connecting alternative pipelines, consisting of:
- PM weld on ring 5 1/2"
- PM clamp coupling 5 1/2"
- PM seal 5 1/2"
Reducer kit, consisting of -reducer 6" - 5 1/2" - 1200mm including 6" coupling and seal
SBU connection
Single agitator motor
OPS control system, with electronic stroke change signals

Optional

Diesel engine, 74KW, Deutz model - F06L0912, Air cooled
RSA- Grill Safety
Compressor 7.5 HP, Max working pressure 12 bar. Air receiver 160L, working pressure 10 bar.

See quotation for exact serial delivery scope.
Comprehensive range of options available on request.