

BSC range for bore pile filling

BSC 1005 D3B

Concrete pressure of up to 71 bar
Delivery volume of up to 58 m³/h



Note: This is a merely informative, non-binding document. Maximum theoretical values listed. Specifications are subject to change without prior notice. Photos and drawings are for illustrative purposes only. For available options, please consult the factory.

Technical data

Dimensions		
Length	mm	5.523
Width	mm	2.018
Height	mm	2.433
Weight	kg	5.000
Putzmeister Concrete Pump		
Delivery volume of up to	m ³ /h	58
Concrete pressure of up to	bar	71
Pump strokes	min	34
Delivery cylinder stroke	mm	1.000
Delivery cylinder diameter	mm	180
Pressure connection	m	5,5" (125)

Hopper		
Capacity	l	350
Maximum noise levels	dB	108
Central lubrication manual		
Rubber collar		
Chassis		
Engine Diesel Deutz, 4 cylinder		
Engine Power	KW (HP)	55 (75)
Engine emission Stage III B / Tier 4f		
Steel crawlers steel, TFW-Fahrtechnik		
Maximum speed	km/h	2
Diesel deposit	l	135
Lights 2 on the hopper, 1 in front		

Technical data

Remote control		
Radio remote control (transport and output)		
Cable remote control (output)		
Cable length	m	10
Cleaning equipment		
Water tank	l	762
Cleaning pump	l/min /bar	50 / 20
Air compressor	l/min	860
Pressured air tank	l	40
Security platform		
Accesories		

Others
Standard coat of paint MB 1227 Yellow
Technical documents 1 paper copy, 1 CD-ROM copy
Tool box
Emergency button

Optionals

Central lubrication Automatic
Electric vibrator

Transport dimensions

