

BSC range for bore pile filling

BSC 1409 D

Concrete pressure of up to 71 bar
Delivery volume of up to 85 m³/h



Note: This is a merely informative, non-binding document. Maximum theoretical values listed. Specifications are subject to change without prior notice. Photos and drawings are for illustrative purposes only. For available options, please consult the factory.

Technical data

Dimensions		
Length	mm	5.310
Width	mm	1.900
Height	mm	2.245
Weight	kg	6.000
Putzmeister Concrete Pump		
Delivery volume of up to	m ³ /h	85
Concrete pressure of up to	bar	71
Pump strokes	min	32
Delivery cylinder stroke	mm	1.400
Delivery cylinder diameter	mm	200
Pressure connection	m	5,5" (125)

Hopper		
Capacity	l	600
Maximum noise levels	dB	116
Central lubrication manual		
Rubber collar		
Chassis		
Engine Diesel Deutz, 4 cylinder		
Engine Power	kW (HP)	129 (174)
Engine emission Stage III A		
Steel crawlers steel, TFW-Fahrtechnik		
Maximum speed	km/h	2
Diesel deposit	l	135
Lights 2 on the hopper		

Technical data

Remote control		
Radio remote control (transport)		
Cable remote control (output)		
Cable length	m	10
Cleaning equipment		
Water tank	l	500
Cleaning pump	l/min /bar	50 / 20
Air compressor	l/min	860
Pressured air tank	l	40
Accessories		

Others	
Standard coat of paint MB 1227 Yellow	
Technical documents 1 paper copy, 1 CD-ROM copy	
Tool box	
Emergency button	
Electric vibrator	

Optionals

Automatic central lubrication
High pressure water pump
Radio remote control
Special coat of paint Doors, pipes & mud guard

Transport dimensions

