



Putzmeister

Your benefits

- Up to 15 % lower fuel consumption through optimised compressor unit
- Noise emission reduced by up to 2 dB
- Hydraulic feeder to work more efficiently
- Scaper to fill easily
- Operating panel clear and user-friendly
- Integrated toolbox: Tools required are always to hand
- Chassis with automatic brake adjustment
- Optimised maintenance and service features
- Robust design ensures value retention and high resale values
- Made in Germany

Mixokret M 740 – Durable and strong



The Mixokret M 740 is fitted with a powerful drive unit, which saves fuel and ensures a more conserving and uniform pump performance. The result is a constant material flow and less hammer in the hoses.

The powerful screed all-rounder gives you the best operating comfort. The durability and reliability in all parts ensures the best possible availability of your machine.

Made in Germany: Virtually all main and drive components such as the engine and compressor of our Mixokret M 740 are developed and produced in Germany.

Your competent Putzmeister dealer will be happy to advise you on technical details and application issues.

- **Cement screed**
- **Calcium sulphate screed (anhydrite)**
- **Magnesia screed**



Semi-dry
floor screed



Powerful drive unit: Fuel saving and low-wear thanks to automatic engine speed control



High resale value thanks to robustness and made in Germany quality



The innovative exhaust air routing and an additional exhaust duct improve the working area.

Technical data

	M 740 D	M 740 DB	M 740 DBS
Mixer drum	260 l; 200 l useful capacity		
Delivery rate*	3.8 m ³ /h	4.6 m ³ /h	5 m ³ /h
Delivery pressure	8 bar	8 bar	8 bar
Delivery range**	180 m horizontally / 90 m vertically (30 storeys)		
Compressor	4.35 m ³ /min; cut-off pressure 8 bar		
Engine	3-cylinder Deutz diesel; 33.5 kW at 2,500 rpm (not available in the EU)		
Weight (fully fuelled)	1,542 kg	1,740 kg	1,814 kg
Tank capacity	60 l	60 l	60 l
Length	4,780 mm	5,075 mm	5,075 mm
Width	1,480 mm	1,480 mm	1,480 mm
Height	1,520 mm	2,431 mm	2,431 mm
Filling height	820 mm	400 mm	400 mm
Maximum grain size	16 mm	16 mm	16 mm
Chassis	braked, with automatic brake adjustment approved for speeds up to 80 km/h		
Special feature	Basic version	with hydraulic feeder	with hydraulic feeder and scraper

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Equipment

Automatic brake adjustment	■
Car coupling	■
Central lubrication system	■
Discharge stand	■
Grease pump for lubrication system	■
Instruction manual and spare parts list	■
Lever Press with hose	■
Lifting eye	■
Reservoir gauge in control panel	■
Toolbox, integrated (40 l)	■
Working lights	■
Conversion to 100 km/h	□
High-pressure cleaner	□
Light holder 24 V	□
Location system	□
Mixing time adjustment	□
Protective plate for feeder	□
Special canopy paint in RAL colours/Custom labelling	□
Support feet	□
Truck coupling	□
Wear plates at the dome	□
Wear plates front end (impact protection bars)	□
Wear plates, highly wear-resistant (lateral)	□
Wear plates, plastic	□

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
 P.O.Box 2152 · 72629 Aichtal / Germany
 Tel. +49 7127 599-0 · Fax +49 7127 599-743
 mm@pmw.de · www.pmmortar.de

