



Putzmeister

Your benefits

- Machine performance management (optional) allows adjustment of engine power as needed – it is possible to save up to 20 % of fuel
- Protected innovative display incl. “Trouble-shooting” and “Service information”
- Kubota diesel engine (Emissions level Stage V) water-cooled, eco-friendly with integrated particle filter for optimised performance
- Optimised maintenance and service features
- Innovative exhaust air routing and additional exhaust duct for improved cooling output and better operability
- Robust design ensures value retention and high resale values
- Made in Germany

Mixokret M 760 Stage V = Eco-friendly + max. Power



Semi-dry
floor screed

- **Cement screed**
- **Calcium sulphate screed** (anhydrite)
- **Magnesia screed**



Special
applications

- Sand
- Aggregate

The M 760 Stage V conveys screed up to 200 metres* horizontally and 150 metres* vertically. The keypad with innovative, colour LED display in the control cabinet makes operation incredibly simple and efficient. The menus for troubleshooting and servicing improve availability.

The Kubota diesel engine (Emissions level Stage V) offers even more power. The integrated diesel particle filter cleans the exhaust gases and protects our environment.

For further information related to technical details or application, please contact your local Putzmeister dealer.



Most powerful Mixokret, with a water-cooled, 4-cylinder Kubota diesel engine and with integrated particle filter.



The 8 button keypad with colour LED display is very clearly arranged and easy to use.



Machine performance management (optional) allows adjustment of engine power as needed. Due to this it is possible to save up to 20 % of fuel.

Technical data

	M 760 DH	M 760 DHB	M 760 DHBS
Mixer drum	260 l, 200 l useful cap.	260 l, 200 l useful cap.	260 l, 200 l useful cap.
Delivery rate*	4 m ³ /h	4.8 m ³ /h	5 m ³ /h
Delivery pressure	8 bar	8 bar	8 bar
Delivery range**	200 m horizontally / 150 m vertically (50 storeys)		
Compressor	5.0 m ³ /min; cut-off pressure 8 bar		
Engine	Kubota 4-cylinder diesel, water-cooled 48.5 kW at 2700 rpm, Stage V		
Weight (fully fuelled)	1,720 kg	1,826 kg	1,900 kg
Tank capacity	approx. 70 l	approx. 70 l	approx. 70 l
Length	4,780 mm	5,075 mm	5,075 mm
Width	1,480 mm	1,480 mm	1,480 mm
Height	1,520 mm	2,431 mm	2,431 mm
Filling height	820 mm	400 mm	400 mm
Maximum grain size	16 mm	16 mm	16 mm
Chassis	braked, approved for speeds up to 80 km/h		
Special feature	Basis version	with hydraulic feeder	with hydraulic feeder and scraper

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Equipment

Working lights	■
Discharge stand	■
Instruction manual and spare parts list	■
Grease pump for lubrication system	■
Central lubrication system	■
Lever Press with hose	■
Lifting eye	■
Car coupling	■
Fuel gauge in display	■
Auto-Power-Off	□
Filling-level probe central grease lubrication	□
High-pressure cleaner	□
Light holder 24 V	□
Truck coupling	□
Performance management	□
Mixing time adjustment	□
Location system	□
Protection plate for feeder	□
Special canopy paint in RAL colours/Custom labelling	□
Support feet	□
Conversion to 100 km/h	□
Wear plates at the dome	□
Wear plates (Hardox 6 mm)	□
Wear plates (Hardox 8 mm)	□
Wear plates plastic	□
Wear plates at front end	□
Water dosage	□

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
P.O.Box 2152 · 72629 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
mm@putzmeister.com · www.putzmeister.com

