



Putzmeister

Your benefits

- Maintenance and service-friendly: everything is protected below the canopy
- Operating panel ergonomical on one side
- Large hopper 280 l with rubber collar and protective grid
- Piston pump unit extremely robust
- Chassis for road use with automatic brake adjustment
- Supporting feet for secure stability
- Made in Germany

P 715 – Reliable, powerful and mobile for a wide range of applications



Self levelling floor screed

- Calcium sulphate screed
- Cement floor screed



Shotcrete

- Shotcrete



Fine grained concrete

- Conveying fine grained concrete
- Grouting work




The P 715 can reliably convey up to 16 mm pumpable media over considerable distances. The powerful piston pump is ideal for shotcrete and liquid screed applications.

With a delivery pressure of up to 68 bar and an output of 18 m³/h, it is a real power pump, despite its small dimensions and low weight.

Putzmeister will be happy to explain the additional advantages to you and answer all your questions with regard to your individual requirements.



Fine concrete pumps like the P 715 are among the most versatile systems. You can use them for shotcrete or for pumping fine concrete of up to 16 mm.



Two drive versions: Reliable oil-cooled 3-cylinder Deutz diesel engine complies with exhaust emission regulation (Stage 3A) or low-noise, environmentally friendly electric motor (30 kW)



The easy to read, analog instruments and robust switches are protected by a sturdy flap against dirt and the risk of being damaged.

Technical data

P 715 TD

P 715 TE

Feed hopper	250 l / 280 l (with rubber attachment collar)	
Theoretical delivery rate*	4–17.4 m ³ /h	4–18.2 m ³ /h
Delivery pressure	68 bar	68 bar
Delivery range**	max. 300 m horizontal and 100 m vertical; with shotcrete/fine grained concrete, max. 100 m horizontal and 80 m vertical	
Piston pump	Hydraulic, 2-cylinder	
Cylinder diameter	150 mm	150 mm
Drive	3-cylinder Deutz diesel engine, D L03 2011, 34.5 kW	30 kW electric motor, 400 V, 50 Hz
Drive cylinder diameter	80/45 mm	80/45 mm
Piston stroke	700 mm	700 mm
Min. strokes	27	27
Weight	1850 kg (TD)	1800 kg (TE)
Length x width x height	4600 x 1520 x 1750 mm (TD)	4600 x 1520 x 1650 mm (TE)
Filling height	1180 mm (TD)	1180 mm (TE)
Maximum particle size	16 mm	16 mm
Machine model	Trailer pump (TD and TE)	
Chassis	T chassis 1900 kg (TD and TE)	

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and is dependent on the materials used.

Equipment

Autom. brake adjustment	■
Car fuse	■
Clamp coupling with sealing 4,5"	■
Cleaning tool	■
Instruction manual and spare parts list	■
Protective grid	■
Protective helmet	■
Rubber collar	■
Tool box with tool	■
Vibrator	■
Additive metering	□
Air vessel (self levelling floor screed)	□
Cable remote control	□
Central lubrication system	□
Exhaust flap	□
Flushing water pump	□
High-pressure cleaner	□
Lifting eye	□
Light holder 24 V	□
Working light	□

□ Option ■ Standard

Putzmeister Concrete Machines Pvt. Ltd.

Plot No. N4, Phase 4, Verna Industrial Estate,
Salcette - Goa 403 722. INDIA

Tel. +91 (832) 6696 000

Fax +91 (832) 6696 300

www.putzmeister.com



For all your support needs, contact - **Sales:** sales@pmw.co.in | **Service:** aps@pmw.co.in

Regional Offices: **NORTH:** 011 4200 5600, **EAST:** 033 6614 2525, **WEST:** 022 2636 0181 / 82, **SOUTH:** 040 4010 1015